

2\7\2026

قيمة كلفة تجهيزات سيارات النقل المباشر SNG

سنة 2007	SNG CADILLAC	قيمة كلفة تجهيزات
		قيمة التجهيزات داخل السيارة
200,000\$		RF Section
24,000\$		Video & Audio Section
3000\$		قيمة مولد كهرباء للسيارة
3000\$		قيمة UPS
230,000\$		مجموع الكلفة :


سنة 2014	SNG SUBURBAN	قيمة كلفة تجهيزات
		قيمة التجهيزات داخل السيارة :
200,000\$		RF Section
57,000\$		Video & Audio Section
3000\$		قيمة مولد كهرباء للسيارة
3000\$		قيمة UPS
263,000\$		مجموع الكلفة :

سنة 2015	SNG FORD	قيمة كلفة تجهيزات
		قيمة التجهيزات داخل السيارة:
200,000\$		RF Section
16,000\$		Video & Audio section
3000\$		قيمة مولد كهرباء للسيارة
3000\$		قيمة UPS
222,000\$		مجموع الكلفة :

قيمة كلفة أجهزة النقل المباشر Aviwest DMNG

100,000\$	4 Transmitters
40,000\$	2 Receivers
140,000\$	مجموع الكلفة :

مدير الإرسال الأرضي والبث الفضائي


المهندس سعيد أبو ضاهر
02-07-2026

رئيس تأمين هذه المعدات
عبر بوليصة
Electronic Equipment Insurance

Broadcasting material for SNG Cadillac

Qty.	Code	Description
1	IGP 45000\$	KU BAND 1.2M MOTORIZED AUTOPOINTING ANTENNA: Drive-Away SNG 1.2m, SMC Offset Dish, Gregorian Dual Optic mount type elevation over Azimuth including full fairing protection Azimuth +/- 185. Elevation 10-90. & Polarization +/- 95". Capable of 1:1 400W KU Band (can be fixed inside fairing) with its related accessories. <ul style="list-style-type: none"> • 3 Axis Jog controllers with auto stow/deploy. • 1 Point Option featuring Auto-pointing Controller with built-in GPS and manual 3 axis jog. • Swedish Microwave WDL Dual Output LNB
1	Ericsson EN-8040 45000\$	ERICSSON Encoder unit HD including: <ul style="list-style-type: none"> • Standard Definition only Video Format support; MPEG2/MPEG4 8bit 4:2:2/4:2:0 Video Compression; chassis and power supply; analog composite and digital (SDI & HD-SDI) video input; analog and digital audio inputs; 2 pairs of MPEG Layer II or pass-through audio encoding; 2x ASI and 1x Ethernet outputs. Video Format and Video Compression Licenses. • TITAN-HW-IM-MOD Titan Hardware Interface Module - Internal Modulator - L-Band (with 10MHz reference) and IF (70 & 140 MHz) Outputs, DVB-S (QPSK), DVB-S2 (QPSK, 8PSK, 16APSK) and DVB DSNG (QPSK, 8PSK, 16QAM)
1	XTD-400K 90000\$	Xicom 400W KU Band Digital External HPA , with internal Block Up-converter, 10MHz Reference, Input frequency 950-1700MHz Output frequency 13.75-14.5GHz, Compact, Light Weight rugged enclosure.
1	XTD-400K 2500\$	Dual Thread Controller
1	DCH-5100P 2500\$	IRDMPEG2, MPEG4, HD/SD Output ASI, Analog and Digital Audio Video Output and SDI.
1	RG001LES12 5000\$	Promax HDR Ranger Spectrum Analyzer with built-in Audio Video Decoder
1	X50-AV-2PS 5000\$	Selenio X50 IRU Frame Synchronizer / Converter, HD/SD Formats including 3Gb/S 1080p
2	HDL-SVDUO 2500\$	Blackmagic HDL-SMT VDUO Smartview Dual 8 inch Intelligent SDI Rack
1	ACC-KIT 2500\$	Accessories Kit including Coaxial Cables, Flexible Twistable Waveguides and related connectors.
1	CB-TL-282/1 24000\$	(Audio & video section)
1	EX 3000 RT 3000\$	UPS-3KVA Rack Mount UPS with separate Rack Mount Battery cabinet. Housing 16x7 Ah 12V Battery
1	EU3000 3000\$	Honda Silent 3KVA Generator with Inverter Technology.

مدير الإرسال الأرضي والبث الفضائي


 المهندس سعيد أبو ضاهر

Broadcasting material for SNG Suburban

Qty.	Code	Description
1	RM120 45000\$	KU BAND 1.2M MOTORIZED AUTOPOINTING ANTENNA: Holkirk RM120 Drive-Away SNG 1.2m, SMC Offset Dish, Gregorian Dual Optic mount type elevation over Azimuth including full fairing protection Azimuth +/- 185. Elevation 10-90. & Polarization +/- 95". Capable of 1:1 400W KU Band (can be fixed inside fairing) with its related accessories. <ul style="list-style-type: none"> • 3 Axis Jog controllers with auto stow/deploy. • 1 Point Option featuring Auto-pointing Controller with built-in GPS and manual 3 axis jog. • Swedish Microwave WDL Dual Output LNB
1	TITAN-2 45000\$	TITAN Three Encoder unit HD including: <ul style="list-style-type: none"> • Standard Definition only Video Format support; MPEG2/MPEG4 8bit 4:2:2/4:2:0 Video Compression; chassis and power supply; analog composite and digital (SDI & HD-SDI) video input; analog and digital audio inputs; 2 pairs of MPEG Layer II or pass-through audio encoding; 2x ASI and 1 x Ethernet outputs. Video Format and Video Compression Licenses. • TITAN-HW-IM-MOD Titan Hardware Interface Module – Internal Modulator – L-Band (with 10MHz reference) and IF (70 & 140 MHz) Outputs, DVB-S (QPSK), DVB-S2 (QPSK, 8PSK, 16APSK) and DVB DSN (QPSK, 8PSK, 16QAM)
1	XTD-400K 90000\$	Xicom 400W KU Band Digital External HPA , with internal Block Up-converter, 10MHz Reference, Input frequency 950-1700MHz Output frequency 13.75-14.5GHz, Compact, Light Weight rugged enclosure.
1	XTD-400K 2500\$	Dual Thread Controller
1	DCH-5100P 2500\$	IRD MPEG2, MPEG4, HD/SD Output ASI, Analog and Digital Audio Video Output and SDI.
1	RG001LES12 5000\$	Promax HDR Ranger Spectrum Analyzer with built-in Audio Video Decoder
1	X50-AV-2PS 5000\$	Selenio X50 IRU Frame Synchronizer / Converter, HD/SD Formats including 3Gb/S 1080p
2	HDL-SVDUO 2500\$	Blackmagic HDL-SMTVDUO Smartview Dual 8 inch Intelligent SDI Rack
1	ACC-KIT 2500\$	Accessories Kit including Coaxial Cables, Flexible Twistable Waveguides and related connectors.
1	CB-TL-282/1 57727\$	(Audio & video section)
1	EX 3000 RT 3000\$	UPS-3KVA Rack Mount UPS with separate Rack Mount Battery cabinet. Housing 16x7 Ah 12V Battery
1	EU3000 3000\$	Honda Silent 3KVA Generator with Inverter Technology.

مدير الإرسال الأرضي والبث الفضائي

المهندس سمير أبو ضاهر

Broadcasting material for SNG Ford

Qty.	Code	Description
1	RM120 45000\$	KU BAND 1.2M MOTORIZED AUTOPOINTING ANTENNA: Holkirk RM120 Drive-Away SNG 1.2m, SMC offset Dish, Gregorian Dual Optic mount type elevation over Azimuth including full fairing protection Azimuth +/- 185 . Elevation 10-90 . & Polarization +/- 95" . Capable of 1:1 400W KU Band (can be fixed inside fairing) with its related accessories. <ul style="list-style-type: none"> • 3 Axis Jog controllers with auto stow/ deploy . • 1 Point Option featuring Auto-pointing Controller with built-in GPS and manual 3 axis jog . • Swedish Microwave WDL Dual Output LNB
1	TITAN-3 45000\$	TITAN Three Encoder unit HD including: <ul style="list-style-type: none"> • Standard Definition only Video Format support; MPEG2/MPEG4 8bit 4:2:2/4:2:0 Video Compression; chassis and power supply; analog composite and digital (SDI & HD-SDI) video input; analog and digital audio inputs; 2 pairs of MPEG Layer II or pass-through audio encoding; 2x ASI and 1x Ethernet outputs. Video Format and Video Compression Licenses. • TITAN-HW-IM-MOD Titan Hardware Interface Module – Internal Modulator -L-Band (with 10MHz reference) and IF (70 & 140 MHz) Outputs, DVB-S (QPSK), DVB-S2 (QPSK, 8PSK, 16APSK) and DVB DSN (QPSK, 8PSK, 16QAM)
1	ST-180KU1DU 90000\$	Stellar 400W KU Band Digital External HPA , with internal Block Up-converter, 10MHz Reference, Input frequency 950-1700MHz Output frequency 13.75-14.5GHz, Compact, Light Weight rugged enclosure.
1	ST-N6081 2500\$	Stellar Single Thread Controller
1	DCH-5100P 2500\$	IRD MPEG2, MPEG4, HD/SD Output ASI, Analog and Digital Audio Video Output and SDI.
1	RG001LES12 5000\$	Promax HDR Ranger Spectrum Analyzer with built-in Audio Video Decoder
1	X50-AV-2PS 5000\$	Selenio X50 IRU Frame Synchronizer / Converter, HD/SD Formats including 3Gb/S 1080p
2	HDL-SVDUO 2500\$	Blackmagic HDL-SMT VDUO Smartview Dual 8 inch Intelligent SDI Rack
1	ACC-KIT 2500\$	Accessories Kit including Coaxial Cables, Flexible Twistable Waveguides and related connectors.
1	CB-TL-282/1 16000\$	(Audio & video section)
1	EX 3000 RT 3000\$	UPS-3KVA Rack Mount UPS with separate Rack Mount Battery cabinet. Housing 16x7 Ah 12V Battery
1	EU3000 3000\$	Honda Silent 3KVA Generator with Inverter Technology.

مدير الإرسال الأرضي والبث الفضائي


المهندس سعيد أبو ضاهر

Recommended Broadcasting DMNG

By 4G Packages

Item	Description		Price
A	4 Transmitter	DMNG By 4G Packages (SDI/HDMI input ,1080p support.8 embedded modems up to 4 USB modem ports, Inverse Statmux+ (IS+) technology, on - board storage,dual band WiFi card,removable internal battery ,AC power supply ,and carrying case); including: Standard software:includes 0.5 hours of HD recording .Does not enabled use of any USB modems. - Backpack with mount for V-Mount external battery in the lower compartment of the backpack.	100,00\$
B	2 Reciever	Receiver rack-mount (IU) high-power server with internal power supply and four SDI connectors, including Basic Receiver software with Linux operating system , supporting single SDI output .Must be upgraded to Advanced software before any upgrades can be Purchased.	40,000\$

مدير الإرسال الأرضي والبيث الفضائي


المهندس سعيد أبو ضاهر